



**Application**

Designed to achieve minimal clearances of just 3mm between the top edge of the door and underside of the track concealing all moving parts.

Ideally suited to floor to ceiling straight sliding timber doors in both residential and commercial applications.

Zero Clearance 180 hangers are cast 316 stainless steel with stainless steel bearings and suitable for both interior and exterior and exterior applications.

**Door Specification**

**Track System:**

For Individual Doors:  
Max Leaf Height  
Max Leaf Weight  
Min Door Thickness

**Zero Clearance 180**

3000mm  
180kg  
35mm

For ease of operation it is recommended that the door width should not exceed 75% of the height of the door. Timber doors for interior use can be flush construction or glazed.

**Hardware Specification**

**Track:**

Material  
Standard Lengths

180  
Aluminium Clear Anodised  
2000mm, 3000mm, 4000mm and 6000mm

**Hangers:**

Timber doors  
Stainless steel hangers are fitted with nylon tyre wheels on precision stainless steel ball bearings. Vertical adjustment is simple and positive.

61GN

**Guides:**

Timber Doors  
Sawcut Guide  
Stainless precision bearing  
Nylon spring load guide  
Multiple Doors  
Spring Guide

101N  
106E/94  
108N/814  
102W/94SS  
801S

**Channels:**

Aluminium

94A Aluminium  
94P Polypropylene - Black  
94PPA Aluminium support & Polypropylene  
814 Aluminium Rail  
Aluminium - Mill or Clear Anodised  
2000mm, 3000mm, 4000mm and 6000mm

**Finish**

Standard lengths

**Accessories:**

Flush Pulls  
Door Stop  
Locking

401  
180DS  
6400 Series Sliding mortice locks  
456 Flush Bolts

**Finishes:**

PVD Brass, Satin Nickel & Polished Nickel



