



Application

Designed to achieve minimal clearances of just 3mm between the top edge of the door and underside of the track concealing all moving parts.

Ideally suited to floor to ceiling straight sliding timber doors in both residential and commercial applications.

Zero Clearance 350 hangers are cast 316 stainless steel with stainless steel bearings and suitable for both interior and exterior and exterior applications.

Door Specification

Track System:

For Individual Doors:
 Max Leaf Height
 Max Leaf Weight
 Min Door Thickness

Zero Clearance 350

3000mm
 350kg
 35mm

For ease of operation it is recommended that the door width should not exceed 75% of the height of the door. Timber doors for interior use can be flush construction or glazed.

Hardware Specification

Track:

Material
 Standard Lengths

250
 Aluminium Clear Anodised
 2000mm, 3000mm, 4000mm and 6000mm

Hangers:

Timber doors
 Stainless steel hangers are fitted with nylon tyre wheels on precision stainless steel ball bearings. Vertical adjustment is simple and positive.

61HN

Guides:

Timber Doors
 Sawcut Guide
 Stainless precision bearing
 Nylon spring load guide
 Multiple Doors
 Spring Guide

101N
 106E/94
 108N/814
 102W/94SS
 801S

Channels:

Aluminium

94A Aluminium
 94P Polypropylene - Black
 94PPA Aluminium support & Polypropylene
 814 Aluminium Rail
 Aluminium - Mill or Clear Anodised
 2000mm, 3000mm, 4000mm and 6000mm

Finish

Standard lengths

Accessories:

Flush Pulls
 Door Stop
 Locking

401
 180DS
 6400 Series Sliding mortice locks
 456 Flush Bolts

Finishes:

PVD Brass, Satin Nickel & Polished Nickel



